

## debelle®

## Manual & Automatic Powder Coating Solutions

www.debellepowdercoating.com

### FOSHAN DEBELLE TECHNOLOGY CO.,LTD.

Website:www.debellepowdercoating.com

Email:sales@debellepowdercoating.com

Whatsapp/Phone:+86-13690635085

Factory Address: Building 11,Liandong U Valley,Nansha Community,Danzao Town,Nanhai District, Foshan,China Shenzhen Office Address: Room 908,Chengtou Xinshidai Building,No.2009 Pingshan Avenue,Liulian Community,Pingshan Street,Pingshan District,Shenzhen,China



### **About us**

Foshan Debelle Technology Co., Ltd. is a manufacturer of manual and automatic electrostatic powder coating machines and guns. We provide complete powder coating solutions with superior quality, precision, and efficiency.

With 37 offices worldwide, we provide integrated services from R&D, production to after-sales service. We have a 10,000 sqm factory and dust-free workshop.

Our products serve diverse end markets, specifically in aluminum profile, wood and MDF, automotive, furniture, white appliances, protective coating, new energy, etc.

20 Years+

Rich experiences

Total floorplant

10,000 m<sup>2</sup>+

50+

National Patents for controller/gun/pump/tube etc.

13+

Invention Patents for vaious inner components.

10,000+

**Global Customers** 

TOP SALES AMOUNT IN THE INDUSTRY for 3 YEARS

### Workshop







First Anti-electrostatic Dust-free Workshop In the industrial







### **Teams**












NαD Tealli

## **Certificates & Patents**



## **Global Customers**



## **Contents**


Company info	01
Workshop	02
Teams	02
Certificates	03
Global Customers	03
Contents	04
Coating Plant	0
Applications	0(
T30-L Auto Coating Machine	7-8
E7 Auto Coating Machine	9-10
T30-L Manual Coating Machine	11-12
E7 Manual Coating Machine	13-14



### Provide one-stop solutions for all coating problems.

Whenever you trying to developing new production line or looking for a breakthrough in surface treatment, debelle provide you with one stop solutions for all these problems. After more than 20 years of development in powder coating business. debelle provides you with the most comprehensive coating solutions, from pretreatment to final packing.

Welcome to consult with us anytime.



### **APPLICATION**





**Thickness measurement film** 



**Appliance** 

**Aluminium Profile** 



Grooves



**Bicycle** 



**Wheels and Rims** 

## **Auto Powder Coating Machine** T30-L Model

√ 3 Smart control mode for beginner

All data is pre-set. One touch of the button could work perfectly without further adjustment.

√ Change color in one touch of button

Changing color within 1 minute. One touch of the button will auto-clean gun/pump/residue in tube.

✓ Enhance production efficiency

up to 5 meters/minute and run for 24 hours fully loaded











		ontroller Specification		
Size	17.5*17.5*25CM			
G.W.	3762G			
Input Voltage	100-240VAC			
Input Frequency	50hz			
Rated Power				
Solenoid valve control voltage	35W			
		24VDC		
Working Air pressure		6-8KG		
Air consumption		≤ 0.3m³/min		
Control		LCD screen		
Working Temperature	-20℃ - 50℃			
Display		LCD		
	T30-L Auto Gu	In Specification		
Size	44*60*4.2cm			
G.W.		610G		
Waterproof level		IP54		
Input voltage				
Output voltage	12vdc			
Output current	0-100KV			
Coating rate per times	0-100μΑ			
	80%			
Powder output volume	500G/minute			
Electrostatic output frequency		29KHZ		
Nozzle Options	Flat with needle			
	Round with needle			
Installation	Mounting			
Support Powder Type Smooth powder/sandy powder/metallic powder				
	T30 Controller Cab	inet (Sell sperately)		
NO.	Size	Pressure stabilization and filtration	Master control system	
12 box Cabinet	135.5*61*60cm		Optional	
24 box Cabinet	171.5*78*60cm	10kg pressure regulating valve (1Mpa)	Optional	
30 box Cabinet	171.5*96*60cm	` ' '	Optional	
	Packing	g Details		
9 9 8 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	<u> </u>		] /	





Powder Tube \*15m



Air tube Red/Black







Box Cabinet\*1 (Sell Seperatel)

### debelle®

Box Cabinet\*1

# **Auto Powder Coating Machine E7 Model**

#### ✓ Auto Adjustment

Auto adjust voltage and current in order to achieve the best coating effect depending on the distance between the coating gun and product.

### √ Easy Operation

A simple of the adjustment valve to control the power output volume/atomization/current and voltage.

#### ✓ Stable And Durable

All machine components are using an top international brand. It is reliable and long-lasting quality.









	E7 Model Auto Con	troller Specification			
Size	17.5*17.5*26CM				
G.W.	5950G				
Input Voltage	220VAC				
Input Frequency	50hz				
Rated Power	50W				
olenoid valve control voltage	24VDC				
Working Air pressure	6-8KG				
Air consumption		≤ 0.3m³/min			
Control		Valva control			
Working Temperature		<b>-20</b> ℃ <b>- 50</b> ℃			
Display		Digital light+barometer			
	E7 Auto Gun	Specification			
Size	-				
G.W.		610G			
Waterproof level		IP54			
Input voltage	12vdc				
Output voltage	0-85KV				
Output current	0-100μΑ				
Coating rate per times		80%			
Powder output volume	500G/minute				
Nozzle Options	Flat nozzle with electro needle				
Nozzie Options		Round nozzle with electro needle	)		
Installation		Mounting			
Support Powder Type	Smoot	h powder/sandy powder/metallic	powder		
	E7 Controller Cabi	net (Sell sperately)			
NO.	Size	Pressure stabilization and filtration	Master control system		
15 box Cabinet	144*61*50cm		NOT Support		
24 box Cabinet	180*78*60cm	10kg pressure regulating valve (1Mpa)	NOT Support		
30 box Cabinet	180*91*60cm		NOT Support		
	Packing	Details			
		debelle debell	Powder Powder		

Locking Sleeve\*1 Coating Gun cable\*15m Powder Tube \*15m Air tube Red/Black Ground Cable\*1



# Manual Powder Coating Machine T30-L Model

### **✓ Straightforward Parameter**

Digital screen showing key parameters in realtime, easy control coating details, lower defect rate.

#### **✓ Bigger Powder Volume**

Powder output volume for flat board parts could be up to 500G/minute, higher efficiency on coating with lower defect rate.

### **✓ Intelligent Program Storage**

T30-L is fully designed and patented by Debelle, provide 20 storage program for different products coating.







	T30-L Mode	el Manual Cor	ntroller Specifi	cation	
Size			17.5*17.5*25C	M	
G.W.			4KG		
Input Voltage			100-240VAC		
Input Frequency			50hz		
Rated Power			35W		
Solenoid valve control voltage			24VDC		
Working Air pressure			6-8KG		
Air consumption			≤ 0.3m³/min		
Control			CNC Adjustme	nt	
Working Temperature			-20℃ - 50℃		
Display			LCD		
	T30-l	L Manual Gun	Specification		
Size			36*23*3.7cm		
G.W.			385G		
Waterproof level			IP54		
Input voltage			12vdc		
Output voltage		0-100KV			
Output current		0-100μΑ			
Coating rate per times	80%				
Powder output volume	500G/minute				
Electrostatic output frequency	29Khz				
	Flat nozzle with electric needle				
Nozzle option	Round nozzle with electric needle				
	Extension pole				
Support Powder Type		Smooth p	owder/sandy powde	r/metallic powder	
Packing Details					
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0				Contraction of the state of the	
T30-L Auto V12 Controller*1	Coating Gun*1	Stroller*1	Barrel*1	Powder Pump*1	Extent nozzle with needle*1
Venturi Tube*3 Lockir	ng Sleeve(V12)*1	Trumpet nozzle (S/M/L)	Flat nozzle with needle*1	Electrode needle *1	Ground Cable*1
Powder Tube *1 Air	ir Tube *1	Fludization Tube *15m	Air tube Red/Black	Powder suction roc	l*1



# Manual Powder Coating Machine **E7 Model**

### ✓ Auto Adjustment

500g/min Big powder output volume, softe output for high efficient and even coating.

### **✓ Easy Operation**

A simple of the adjustment valve to control the power output volume/atomization/current and voltage.

#### √ Stable And Durable

All machine components are using TOP international brand, make sure its reliable and long-lasting quality.







	E7 Mode	I Manual Cont	roller Specifi	cation	
Size		24*18*26.5CM			
G.W.		5.9KG			
Input Voltage		100-240VAC			
Input Frequency			50hz		
Rated Power			50W		
Solenoid valve control voltage	•		24VDC		
Working Air pressure			6-8KG		
Air consumption			≤ 0.3m³/mi	n	
Control			Valve		
Working Temperature			-20°C - 50°C		
Voltage Display			Digital tube+bar	meter	
	E7	' Manual Gun	-		
Size			36*23*3.7c	m	
G.W.			380G		
Waterproof level			IP54		
Input voltage		12vdc			
Output voltage			0-85KV		
Output current		0-100μΑ			
Coating rate per times  Powder output volume		80%			
Powder output volume		500G/minute			
		Flat with needle			
Nozzle Options		Round with needle			
		Extended pole			
Support Powder Type		Smooth powder/sandy powder/metallic powder			
		Packing D	etails		
	T	non-re-compa		Control of the Contro	•
E7 Auto E7 Controller*1	Coating Gun*1	Stroller*1	Barrel*1	Powder Pump*1	Powder suction tube*1
Venturi Tube*3 Lockin	ng Sleeve(V12)*1	Locking Sleeve(E7)*1	Trumpet nozzle (S/M/L)	Flat nozzle with needle*1	Electrode needle *1
Extent nozzle with needle*1	wder Tube *1	Air Tube *1	Fludization Tube	Air tube Red/Black	Ground Cable*1